

TS Series Technical Specs

Model	Nom Imped.	Fs (Hz)	Re (Ohm)	Le (mH)	QMS	QES	QTS	VAS cu.ft	VAS liter	Power Watts RMS	Power Watts Peak	SPL db@ 1w/1m	X-Max inches	X-Max mm	Max Vented	Port Round	Min Vented	Port Round	Max Sealed	Min Sealed
-------	------------	---------	----------	---------	-----	-----	-----	-----------	-----------	-----------------	------------------	---------------	--------------	----------	------------	------------	------------	------------	------------	------------

TS-AR Series

TS-AR10	4	34	3.6	3.0	9.35	0.49	0.51	1.2	34	250	500	88	0.30	7.5	2.0	2 X 6	1.0	2 X 6	1.4	0.9
TS-AR12	4	30	3.6	2.9	11.4	0.47	0.50	2.64	74.9	3100	1000	90	0.30	7.5	3.4	3 X 8	1.8	3 X 6	2.8	1.5
TS-AR15	4	25	3.6	1.56	7.0	0.49	0.47	7.1	240	425	850	95	0.30	7.5	4.4	3 X 10	3.7	3 X 8	3.8	3.0

TS-PR Series (all colors)

TS-PR10	2x4	35	3.6	3.0	7.34	.48	0.50	1.31	37.6	250	500	88	0.30	7.5	2.0	2 X 6	1.0	2 X 6	1.4	0.9
TS-PR12	2x4	30	3.6	3.0	7.51	.50	0.48	2.84	81	3100	1000	90	0.30	7.5	3.4	3 X 8	1.8	3 X 6	2.8	1.5
TS-PR15	2x4	25	3.6	1.57	4.56	.54	0.49	5.6	172	425	850	94	0.30	7.5	4.4	3 X 10	3.7	3 X 8	3.8	3.0

TS-VR Series

TS-VR10	2x4	35	2x3.6	1.93	4.53	.60	0.53	1.1	31.7	250	500	86	0.31	8	1.9	2 X 6	1.0	2 X 6	1.3	0.9
TS-VR12	2x4	33	2x3.6	1.85	3.85	.62	0.56	1.9	54.4	3100	1000	88	0.31	8	3.2	3 X 8	1.8	3 X 6	2.7	1.5
TS-VR15	2x4	32	2x3.6	2.0	4.05	.64	0.54	4.17	119	425	850	90	0.31	8	4.3	3 X 10	3.7	3 X 8	3.7	3.0